

Specification Sheet

Part Number: 170-03066



Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Gray, 40 ft/reel

Article Number	170-03066
Type	BSPFR1128
Color	Gray (GY)
Features & Benefits	<ul style="list-style-type: none">• Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.• Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.
Quantity Per	reel
Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
Short Description	Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Gray, 40 ft/reel

Global Part Name

BSPFR1128-PET-GY

Length L (Imperial)

40.0

Length L (Metric)

12.2

Bundle Diameter Min (Imperial)

1.0

Bundle Diameter Min (Metric)

25.4

Bundle Diameter Max (Imperial)

2.125

Bundle Diameter Max (Metric)

53.9

Diameter D (imperial)

1.50

Diameter D (metric)

38.1

Nominal Diameter (Imperial)

1-1/2

Nominal Diameter (Metric)

38.1

Material

Polyester (PET)

Material Shortcut

PET

Flammability

Mil-202 FAR 25 FMVSS 302 UL VW-1

Halogen free

Yes

Operating Temperature (Metric)	-94°F to +257°F (-70°C to +120°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	40
Package Quantity (Metric)	12.19
Customs Number	3926909987
Weight (Metric)	0.358
Weight (Imperial)	0.79