


ATP Industrial Grade 2.5" SATA SSDs

ATP offers various 2.5" SSDs in SLC, MLC and aMLC types with SATA II & SATA III interfaces. ATP SSDs are designed for different applications, including industrial computers, data center, POS, networking, thin clients and other industrial applications.

SATA III SSDs - Velocity SII Pro



The ATP Velocity SII Pro 2.5" SSD with SATA III interface is a best-in-class wide-temp industrial grade SLC SSD solution with enterprise-class features. SII Pro SSD offers outstanding performance and proven reliability, ideal for extreme performance, and consistent data integrity requirement (ATP PowerProtector technology), suited for POS, industrial computers, data center and industrial applications in mission critical, high shock and vibration environments.

Key Features

- Ideal for heavy program/erase applications
- High Performance with SATAIII interface
- Enhanced endurance with Advanced Wear Leveling algorithm
- Built-in hardware-based data protection technology during power failure – PowerProtector
- NSA Compliant SecureErase
- Supports S.M.A.R.T. ATA feature set
- MIL-STD-810G compliant



Life Monitor



PowerProtector



Secure Erase



Shock Resistance

Specifications


Product Name	Velocity SII Pro SSD 2.5" SATA-III
Flash Type	SLC
Density	32GB to 256GB
Performance	Sequential Read up to 520 MB/s
	Sequential Write up to 420 MB/s
	Random Read IOPS up to 78,000
Interface	SATA III 6 Gb/s
Operating Temperature	-40°C to +85°C
Reliability	Advanced Wear Leveling
	TBW** (max.) : 10,240 TB
	MTBF @ 25°C : >2,000,000 hours
Dimensions: LxWxH (mm)	100.0 x 69.9 x 9.2

Ordering Information

Density	Part Number
32GB	AF32GSSCJ-VACXP
64GB	AF64GSSCJ-VACXP
128GB	AF128GSSCJ-VACXP
256GB	AF256GSSCJ-VACXP

** All TBW data listed are under highest sequential write value in each product line. The TBW data are subject to change by density, configuration and customers' applications.

SATA III SSDs - Velocity MV



Utilizing MLC (Multi Level Cell) NAND flash components, the ATP Velocity M V Enterprise Grade SSD is a best-in-class MLC SSD solution with enterprise- class features for cost-sensitive client environment. M V SSD offers outstanding performance and proven reliability, ideal for extreme performance, high data security, and consistent data integrity requirement, suited for POS, industrial computers, data center and industrial applications exposed to high shock and vibration environments.

Key Features

- Designed for enterprise applications requiring high endurance on MLC technology
- High performance with SATA III Interface
- Enhanced endurance with Advanced Wear Leveling algorithm
- Built-in hardware-based data protection technology during power failure – PowerProtector
- NSA Compliant SecureErase
- Supports S.M.A.R.T. ATA feature set
- MIL-STD-810G compliant



Life Monitor



PowerProtector



Secure Erase



Shock Resistance

Specifications

Product Name	Velocity M V 2.5" SSD SATA-III
Flash Type	MLC
Density	64GB to 512GB
Performance	Sequential Read up to 520 MB/s
	Sequential Write up to 440 MB/s
	Random Read IOPS up to 70,000
Interface	SATA III 6 Gb/s
Operating Temperature	0°C to 70°C
Reliability	Advanced Wear Leveling
	TBW** (max.) : 614.4 TB
	MTBF @ 25°C : >2,000,000 hours
Dimensions: LxWxH (mm)	100.0 x 69.9 x 9.2

Ordering Information

Density	Part Number
64GB	AF64GSMCJ-VACXP
128GB	AF128GSMCJ-VACXP
256GB	AF256GSMCJ-VACXP
512GB	AF512GSMCJ-VACXP

** All TBW data listed are under highest sequential write value in each product line. The TBW data are subject to change by density, configuration and customers' applications.

SATA II SSDs - Velocity XE



The ATP Velocity XE SATA SSD provides outstanding performance and proven reliability for product operation, which is perfect for networking and thin clients, and is also suitable for enterprise storage systems with outstanding sequential read and writes performance to relieve performance bottlenecks associated with traditional rotating media storage(HDD).

Key Features

- Designed for enterprise applications requiring high endurance on aMLC (Advanced Multi-Level Cell) technology
- Enhanced endurance by Advanced Wear Leveling algorithm
- Support Static Data Refresh technology
- NSA Compliant SecureErase
- Supports S.M.A.R.T. ATA feature set



Specifications

Product Name	Velocity XE 2.5" SSD SATA-II
Flash Type	aMLC
Density	8GB to 64GB
Performance	Sequential Read up to 250 MB/s
	Sequential Write up to 180 MB/s
	Random Read IOPS up to 4,000
Interface	SATA II 3 Gb/s
Operating Temperature	0°C to +70°C
Reliability	Advanced Wear Leveling
	TBW** (max.) : 1,024 TB
	MTBF @ 25°C : >2,000,000 hours
Dimensions: LxWxH (mm)	100.0 x 69.9 x 9.2

Ordering Information

Density	Part Number
8GB	AF8GSACD-RAAXX
16GB	AF16GSACD-RAAXX
32GB	AF32GSACD-RAAXX
64GB	AF64GSACD-RAAXX

** All TBW data listed are under highest sequential write value in each product line. The TBW data are subject to change by density, configuration and customers' applications.

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368
FAX: +886-2-2659-4982
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
FAX: +1-408-732-5055
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
FAX: +49-89-374-9999-29
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6206-8097
FAX: +81-3-6206-8098
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
FAX: +86-21-9687-0000-026
sales@cn.atpinc.com