

Specification Sheet

Part Number: 170-03092



Braided Sleeving, Expandable, Flame Retardant, .75" Dia, PET, Black, 250 ft/bulk reel

Article Number

170-03092

Type

BSPFR340B

Color

Black (BK)

Features & Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Quantity Per

reel

Product Description

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description

Braided Sleeving, Expandable, Flame Retardant, .75" Dia, PET, Black, 250 ft/bulk reel

Global Part Name

BSPFR340B-PET-BK

Length L (Imperial)

250.0

Length L (Metric)

76.2

Bundle Diameter Min (Imperial)

0.5

Bundle Diameter Min (Metric)

12.7

Bundle Diameter Max (Imperial)

1.25

Bundle Diameter Max (Metric)

31.8

Diameter D (imperial)

0.75

Diameter D (metric)

19.1

Nominal Diameter (Imperial)

3/4

Nominal Diameter (Metric)

19.1

Material

Polyester (PET)

Material Shortcut

PET

Flammability

FMVSS 302 FAR 25 UL 94 V0 UL VW-1 Mil-202

Halogen free Yes

Operating Temperature (Metric) -94°F to +257°F (-70°C to +120°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity(Imperial) 250

Package Quantity (Metric) 76.20

Customs Number 3926909987

Weight (Metric) 1.0

Weight (Imperial) 2.2