

## Specification Sheet

Part Number: RT150MEP0X2



Releasable Cable Tie, Release Tab, 21" Long, 175lb Tensile Strength, PA66, Black, 25/pkg

Article Number	115-00037
Type	RT150MEP
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Special design with extended pawl offers a release feature for quick and easy access to wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton Releasable Cable Ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Releasable Cable Tie, Release Tab, 21" Long, 175lb Tensile Strength, PA66, Black, 25/pkg

**Global Part Name**

RT150MEP-PA66-BK

**Minimum Tensile Strength (Imperial)**

175.0

**Minimum Tensile Strength (Metric)**

780.0

**Length L (Imperial)**

21.0

**Length L (Metric)**

535.0

**Identification Plate Position**

none

**Releasable Closure**

Yes

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.35

**Width W (Metric)**

8.8

**Bundle Diameter Min (Imperial)**

0.32

**Bundle Diameter Min (Metric)**

8.0

**Bundle Diameter Max (Imperial)**

5.9

**Bundle Diameter Max (Metric)**

150.0

<b>Cable Tie Width Max (Imperial)</b>	0.346
<b>Cable Tie Width Max (Metric)</b>	8.8
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987