



NOTES:

1. METAL SHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
2. INSULATORS: PBTP GF UL 94 V-0, BLACK
3. CONNECTOR IS PART MARKED: 3043W2SXK99A10X CONEC ABC

Directive 2002/95/EC
"RoHS"
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			
DO NOT ALTER CAD DRAWING BY HAND			
rev.	description	date	name

tolerance		dim. in mm
date	name	
drawn	12.06.08	Lehmenkühler
appd.	13.06.08	Mickenbecker
norm		
d-old		
a Origin		

scale: 2:1	
material: SEE NOTES	
title: D-SUB COMBINATION FEMALE 43W2S CRIMP STYLE	
dwg no:	Inventor 10
13K1A2527	
part no: 3043W2SXK99A10X	
DIN-A3	sh: 1