

Specification Sheet

Part Number: 148-90038



HelaCon Plus Mini, Push-In Style Wire Connector, Double Spring, 4-Port, (PC), Clear, 100/pkg

Article Number	148-90038
Type	HCPM-4
Color	Clear (CL)
Features & Benefits	<ul style="list-style-type: none">•Spring technology for safe, secure and reliable connections.•Smaller footprint fits in tight spaces.•Low insertion force makes installation of solid or stranded copper wire fast and easy.•Color coded for easy identification of size.•Each port accepts multiple wire diameters for flexible applications.•Accepts 12–22 AWG solid wire and 14–22 AWG stranded wire.
Quantity Per	box
Product Description	<p>HelaCon Plus Mini Wire Connectors replace traditional twist-on wire connectors. They provide faster, easier and more reliable connection and distribution of cable and conductors in electrical installation applications. Mini connectors have a compact footprint and can be applied tool-free using convenient, push-in simplicity. Internal spring technology is approved for solid and stranded wires.</p>

Short Description

HelaCon Plus Mini, Push-In Style Wire Connector, Double Spring, 4-Port, (PC), Clear, 100/pkg

Global Part Name

HCPM-4-PC-CL

Length L (Imperial)

0.65

Length L (Metric)

16.5

Width W (Imperial)

0.76

Width W (Metric)

19.4

Height H (Imperial)

0.30

Height H (Metric)

7.70

Depth D (imperial)

0.65

Depth D (metric)

16.5

Material

Polycarbonate (PC)

Material Shortcut

PC

Flammability

UL 94 V0

Halogen free

Yes

Operating Temperature (Metric)

-22°F to +185°F (-30°C to +85°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL | ANSI/UL 486-A Intertek Semko | EN 60998-2-2:2004 SGS Fimko Ltd | EN 60998-2-2:2004 CE | 2006/65/EC NEMKO AS | EN 60998-2-2:2004 UL | ANSI/UL 486-B SGS Fimko Ltd | EN 60998-2-2:201 ENEC UL | ANSI/UL 486-C cULus

UL Listed (US and Canada) Yes

UL Recognized (US and Canada) Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 100

Content Unit(BMEcat) pcs.