



Specification:
 1. Electrical Char
 Insulation Resistance: 500MΩ min. 500V DC
 for 1 minute
 Contact Resistance: 30mΩ max.
 Rating Current: 1.5A max.
 Rating Voltage: 150V AC
 Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.

2. Physical Char
 Housing: PBT Glass filled (UL 94V-0) Color: Black
 Soldering Temperature: 235°C for 5 sec.
 Spring Wire: 0.45mm Dia Phosphor Bronze
 6u" Gold plating over Nickel
 Temperature Range: -40°C to +85°C
 Durability: 750 mating cycles min.

3. Packing: Tray

RoHS compliant
 Unit:mm

Scale	Free						
TOLERANCE							
.XX	±0.20				Drawn	Date	Name
.XXX	±0.13				Approved	17.07.2018	Amy
.XXXX	±0.05						
DIM	TOL						
		①	Correct PCB size and add detail B	17.07.2018	Amy		
		②	Drawn	28.10.2015	Amy		
Angle	+0°30'		Modification				

Customer-No.	Name	Date	Name
	Amy	28.10.2015	Amy
ASSMANN WSW-No.			
A-2014-2-4-R			
Drawing-No.			
ASS 7043 CO			
Replace	rev01		
	SHEET		



1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	H